

Full steel, HPL or PVC punched tile, surface punched panel which is SPCCID hard steel of Shanghai Bao steel, manual welding for the bottom square tube, origination domestic. Imported paint, conductive rim, pedestal, stringer are pressured forming with steel, lead screw could adjust height.

Sleet HPL Finished Solid Raised Access Floor

- Antistatic, High Dimensional Precision, Fireproof, Higher load capacity, flatness and shockproof
- Elegant appearance for various top tiles like HPL, PVC, ceramic, marble, granite, wood floor
- Agreeable solution to ground air conditioning system
- Recyclable, convenient removing, cost saving, long performance life
- Adjustable height of pedestal, stringer connect, assembly agility.



Sleet HPL Finished Perforated Raised Access Floor

Full steel, HPL or PVC punched tile, surface punched panel which is SPCCID hard steel of Shanghai Bao steel, manual welding for the bottom square tube, origination domestic. Imported paint, conductive rim, pedestal stringer are pressured forming with steel, lead screw could adjust height.



20% ventilation



16% ventilation

- Adjustable height for pedestal, assembly agility, large wire
- High recycled, convenient removing, saving cost
- Prevent static validly, fireproof, dustproof
- 16% ventilation

ANTI-STATIC FIRE RESISTANT C-TRIM EDGE TRIM 1.2MM HPL FINISHED

Application

All kinds of computer room, network service room, monitoring center, electronic workshop, clean room, dustless chamber etc, and occasions demanding antistatic and air conditioning 5A class office, security union plaza, futures trading building, places demanding cabling and wiring and the aging buildings' flooring reform

Ordering Information

Part No.	International	Fire Performance	Size(mm)	Concentrated Load			Impact Load (N)	Ultimate Load (N)	Uniform Load (N/M2)	Rolling Load(N)	
				LB	N	KG				10 times	10000 times
	FS800	A	600x600x35	≥800	≥3350	≥363	≥536	≥11250	≥16100	3560	2670
	FS1000	A	600x600x35	≥1000	≥4550	≥450	≥670	≥13350	≥23000	4450	3560