

Short Depth Full HD 18.5" Widescreen LCD Stacking VGA KVM (with USB VGA Cables)

Featuring an integrated 18.5" LED-backlit widescreen LCD Monitor, keyboard and touchpad in a 1U rack mountable housing. It allows access and control up to 8 computers and up to 256 computers by cascading daisy-chain cable from a single console.



The console supports 1920x1080@60Hz (Full HD) resolution and switching between Computers can be

easily accomplished by front panel pushbuttons, keyboard hotkey combination or on-screen-display (OSD). The console supports both USB and PS2-VGA connection and an additional HDB15 port allows VGA monitor to be connected.

FULL HD RESOLUTION

Widescreen 18.5" LED LCD panel with a 16: 9 aspect ratio delivers resolutions up to 1920x1080 @60Hz

SECURITY

Authorized users can view and control computers and an administrator with a separate profile for each.

PHYSICAL STACKING

Supports Cascading to connect another 31 switches to control up to 256 servers

Features

- Integrated with 8/16 Port KVM switch in 1U height console
- Convenient computer switching via front panel LEDs, keyboard hotkey combination or on-screen display (OSD)
- Supports broadcast mode for keyboard operations simultaneously performed on all selected computers
- Hot pluggable supports to add or remove computers without having to power down the switch
- On-Screen Display (OSD) adjustments – Adjust the on-screen image, including: auto adjust, exit, power on/off, brightness, menu, and a power indicator
- Full size 99 Keys Keyboard with integrated number pad
- Auto scan feature for monitoring user-selected computer
- Quickly select computer by naming the server or inputting SN number of the server
- Supports two level password security. Authorized users can view and control computers and administrators with a separate profile for each.
- Built-in Touchpad with trackball - Eliminates the need for a separate and external mouse
- Compatible with Windows, Sun, Unix and Linux

Reference Electrical Characteristics:

Computer Connections	Direct	8 or 16
	Maximum by Cascading	256
Port emulation	Keyboard & Mouse	PS/2, USB
LCD Monitor	LCD Model	FHD TFT
	Viewing Area	18.5"
	Optimum Resolution	1920×1080@60Hz
	Display Color	16.7 M
	Brightness	350cd/m ² (T y p)
	Contrast Ratio	1000: 1 (T y p)
	Pixel pitch(mm)	0.213(H) × 0.213 (W)
Mouse	X/Y Resolution	>1000 points / inch, (40 points/mm)
	Scroll Wheel	Support Scroll Wheel Function
Keyboard	99 Keys (82 Main Keys + 17 Independent Numeric)	
Port Selection	Pushbuttons, Hotkeys, OSD Menu	
General Features	Input Power	100V – 240Vac, 50 ~ 60Hz, <1.5A
	Power Consumption	23W
	Operating Temperature	0 ~ 50 °C
	Storage Temperature	-20 ~ 60 °C
	Humidity	0~80% RH, Non-condensing
	Net Weight	11.4kg
	Product Dimension (W×D×H)	448mm×560mm×42.5mm
	Package Dimension (W×D×H)	765mm×615mm×185mm
Optional Power Input	-36V— -72Vdc	

Package Contents

- 1 x LCD VGA KVM Switch
- 1 x Power Cord
- 2 x Mounting Rails
- 8 x USB+VGA KVM Cable
- 1x Cat5 Shield Network Cable
- 1 x Ground Lead
- 1 x Quick Start Guide
- 1 x User's Manual

Ordering Information

Part No	Name of items
SN-KC6808S	Short Depth Full HD 18.5" Widescreen LCD 8-Port Stacking VGA KVM
SN-KC6816S	Short Depth Full HD 18.5" Widescreen LCD 16-Port Stacking VGA KVM